

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
6 March 2003 (06.03.2003)

PCT

(10) International Publication Number
WO 03/019999 A1(51) International Patent Classification: H05K 1/18,
3/32, H01L 23/66Raytheon Company, 2000 E. El Segundo Boulevard, P.O.
Box 902 (E1/E150), El Segundo, CA 90245-0902 (US).
QUAN, Clifton; Raytheon Company, 2000 E. El Segundo
Boulevard, P.O. Box 902 (E1/E150), El Segundo, CA
90245-0902 (US).

(21) International Application Number: PCT/US02/26370

(22) International Filing Date: 16 August 2002 (16.08.2002)


(74) Agent: ALKOV, Leonard A.; Raytheon Company, 2000
E. El Segundo Boulevard, P.O. Box 902 (E1/E150), El Se-
gundo, CA 90245-0902 (US).

(25) Filing Language: English

(26) Publication Language: English

(81) Designated States (national): JP, KR.

(30) Priority Data: 09/935,496 23 August 2001 (23.08.2001) US

(84) Designated States (regional): European patent (AT, BE,
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE, TR).(71) Applicant: RAYTHEON COMPANY [US/US]; Alkov,
Leonard, A., 2000 E. El Segundo Boulevard, P.O. Box 902
(E1/E150), El Segundo, CA 90245-0902 (US).Published:
— with international search report(72) Inventors: DEARDEN, Timothy E.; Raytheon Company,
2000 E. El Segundo Boulevard, P.O. Box 902 (E1/E150),
El Segundo, CA 90245-0902 (US). STITT, Jeffrey J.;For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.(54) Title: LOW COST, LARGE SCALE RF HYBRID PACKAGE FOR SIMPLE ASSEMBLY ONTO MIXED SIGNAL PRINTED
WIRING BOARDS

(57) Abstract: An RF interconnect is incorporated in RF module packages (50) for direct attachment onto a multi-layer PWB (100) using compressible center conductor (fuzz button) interconnects. The module has circuitry operating at microwave frequencies. The module package includes a metal housing (52) including a metal bottom wall structure (54). The module includes a plurality of RF interconnects, which provide RF interconnection between the package (50) and the PWB (100). Each interconnect includes a feedthrough center pin (72) protruding through an opening formed in the metal bottom wall, with isolation provided by a dielectric feedthrough insulator (74). The center pin is surrounded with a ring of shield pins (76) attached to the external surface of the bottom wall of the module housing. The pins are insertable in holes (116a, 116b) formed in the PWB (100), and make contact with fuzz button interconnects (130, 132) disposed in the holes (116a, 116b). Circuitry (148, 150) connects the fuzz button interconnects (130, 132) to appropriate levels (120, 122, 124) of the PWB signal conduction.

WO 03/019999 A1

WO 03/019999

PCT/US02/26370

LOW COST, LARGE SCALE RF HYBRID PACKAGE FOR SIMPLE
ASSEMBLY ONTO MIXED SIGNAL PRINTED WIRING BOARDS

TECHNICAL FIELD OF THE INVENTION

This invention related to microwave circuits, and more particularly to RF interconnect techniques.

BACKGROUND OF THE DISCLOSURE

Known techniques for interconnecting MIC (Microwave Integrated Circuit) modules directly onto RF printed wiring boards (PWBs) includes coaxial cables or ribbons and connectors. The disadvantage to these techniques are size, weight, and cost. There are also reliability issues due to coefficient of thermal expansion (CTE) mismatches associated with the different packaging materials when direct solder and epoxy attach is used to mount these modules onto a PWB.

SUMMARY OF THE DISCLOSURE

This invention offers a new, robust, serviceable and compact approach to microwave packaging. Separate and individual MIC modules can now be easily mounted and removed vertically, saving valuable real estate and height.

WO 03/019999

PCT/US02/26370

2

An RF interconnect is incorporated in RF module packages for direct attachment onto a multi-layer PWB using compressible center conductor (fuzz button) interconnects. The module has circuitry operating at microwave frequencies. The module package includes a metal housing including a metal bottom wall structure. The module includes a plurality of RF interconnects, which provide RF interconnection between the package and the PWB. Each interconnect includes a feedthrough center pin protruding through an opening formed in the metal bottom wall, with isolation provided by a dielectric feedthrough insulator. The center pin is surrounded with a ring of shield pins attached to the external surface of the bottom wall of the module housing. The pins are insertable in holes formed in the PWB, and make contact with fuzz button interconnects disposed in the holes. Circuitry connects the fuzz button interconnects to appropriate levels of the PWB for grounding and RF signal conduction.

20

BRIEF DESCRIPTION OF THE DRAWING

These and other features and advantages of the present invention will become more apparent from the following detailed description of an exemplary embodiment thereof, as illustrated in the accompanying drawings, in which:

FIG. 1A is a bottom external view of a multifunction RF module package embodying aspects of the invention. FIG. 1B is a side, partially-broken away view of the module package of FIG. 1B. FIG. 1C is a top view of the module package of FIG. 1A.

WO 03/019999

PCT/US02/26370

3

FIG. 2 is an isometric cross-sectional view illustrating an RF interconnect in accordance with aspects of the invention.

5 FIG. 3 is a schematic view of an RF center pin surrounding by RF ground pins, in accordance with an aspect of the invention.

FIG. 4 is an exploded cross-sectional view of an RF module package and a mixed signal multi-layer PWB, illustrating the interconnection of these structures.

10 FIG. 5 is a view similar to FIG. 4, but showing the RF module package interconnected with the PWB structure.

FIG. 6 is a top view of a stripline conductor trace surrounded by RF ground pads and plated through holes.

15 DETAILED DESCRIPTION OF THE DISCLOSURE

In accordance with an aspect of the invention, an RF interconnect is incorporated in large multifunction RF module hybrid packages for direct board attachment onto a mixed signal multi-layer PWB using compressible conductor (fuzz button) interconnects. The module hybrid package typically contains one or more hybrid circuits, i.e. active devices mounted on a substrate, in turn mounted in the package housing. The module hybrid package operates at microwave frequencies. The interconnect in accordance with aspects of the invention provides highly reliable connection at elevated temperatures, and does not require use of coaxial cables and connectors.

20 FIGS. 1A-1C depict an exemplary embodiment of a module package 50 embodying the invention. The package 50 includes a metal housing 52 including a metal bottom wall structure 54, with one or more hybrid circuits positioned

WO 03/019999

PCT/US02/26370

4

within. The housing has protruding from the bottom wall an interconnect strip of conventional DC signal pins 60, for mating with corresponding DC connector terminals.

5 The module 50 further includes a plurality of RF interconnects 70 in accordance with the invention, which are adapted to provide RF interconnection between the package 50 and a multi-layer PWB. In an exemplary embodiment, each RF interconnect 70 includes a standard 50 ohm feedthrough center pin 72 (FIG. 2) protruding through an
10 opening 54A formed in the metal bottom wall 54. The pin 72 is secured in the opening and isolated from the metal wall by a glass feedthrough insulator 74. The pin 72 is surrounded with a ring of smaller shield pins 76 attached to the external surface 54B of the bottom wall 54 of the
15 module housing 52. The pins 76 are arranged about the center pin to provide an RF shield about the pin 72, and in this exemplary embodiment are brazed directly to the metal wall 54, while the center pin 72 extends from the 50 ohm glass feedthrough 74.

20 In an exemplary embodiment, four to eight of the smaller pins 76 are disposed around the RF signal pin 72 to assure good ground contact and shielding for operation into the microwave frequency range up to C-band. This is accomplished by choosing the diameter and spacing of the pins 76
25 surrounding the center pin extending for the 50 ohm feedthrough as illustrated in FIG. 3 for the cases of the RF center pin 72 surrounded by four RF ground pins 76 for shielding. Thus, for the case of a center pin 72 having a diameter d , and the four pins 76 are spaced at distance D
30 from adjacent shield pins on the corners of a square, the characteristic impedance of the RF interconnect, is given by:

WO 03/019999

PCT/US02/26370

5

$$Z_0 = (173/\epsilon^{1/2}) \log_{10}(D/0.933d),$$

for $d < D$.

See, "Reference Data for Engineers: Radio, Electronics, Computers and Communications," Seventh Edition, Howard S. Sam & Company, 1985. Additional RF ground pins 76 can be used to surround the RF center pin for improved shielding. These cases can be modeled using available software tools to determine the dimensions for 50 ohm transmission line. These software tools include Hewlett Packard HFSS, Sonnet and Ansoft Eminence.

This technique is different from the conventional ball grid array (BGA) and pin grid array (PGA) packages whose sphere and pins are attached to a dielectric substrate. This module package eliminates the need for coaxial connectors and coaxial cables for the RF interconnection. Another advantage is that the mounting and attachment of the RF and DC/Signal interconnect uses the same assembly process so that all the interconnects can be attached simultaneously. This invention provides a superior interconnect approach to conventional gold bonding operation.

On the PWB side, compressible wire, or "fuzz button," interconnects offer a simple, inexpensive, and test-friendly connection technique in comparison to the use of conventional coaxial connectors to interface the PWB. In an exemplary embodiment, the fuzz button interconnects are fabricated of densely packed thin gold plated wire, in a generally cylindrical configuration to fit into holes drilled into the PWB. The fuzz button interconnects can be smaller and lighter than commercial coaxial connectors, and can be packaged more densely. This technique also enables the package to be field removable and replaceable. An RF

WO 03/019999

PCT/US02/26370

6

gasket may be needed to absorb the z-axis CTE mismatch, but this is inexpensive and easy to obtain. Fuzz buttons have been tested up to 8 W of input power but can potentially handle much higher levels.

5 The fuzz button interconnects are inserted into pre-drilled holes 116A, 116B within the integrated RF/DC or mixed signal PWB 100, as shown in FIG. 4. The PWB 100 includes a plurality of PWB layers, in this example layers 102-114. The layers include layers of dielectric material
10 such as Duroid (TM), a glass-woven Teflon (TM) material, polyimide or epoxy glass. The layers can be fabricated of different materials, depending on the frequency range of the signals carried in the different layers, with Duroid (TM) preferable for high frequency operation. The bottom
15 two layers 114, 112 define a stripline transmission line, including the lower and upper stripline ground planes 120, 122 formed respectively on the bottom surface of layer 114 and the top surface of layer 112. An RF conductor trace 124 is formed on the top surface of layer 114, to provide
20 the stripline conductor trace. An opening 122A is formed in the upper ground plane 122, where an RF interconnect terminal is formed. The holes 116A and 116B are drilled in the PWB layers to a depth extending to the top surface of PWB layer 110. Disposed within each hole is a fuzz button
25 interconnect structure. Thus for the center pin 72, fuzz button interconnect structure 130 is inserted into the hole 116A. For the shield pins 74, fuzz button interconnect structures 132 are respectively disposed in the holes 116B. For the DC signal pins, a hole 140 is drilled into the PWB
30 100 to the top surface of layer 110, and a fuzz button interconnect structure is inserted into the hole 140. At the bottom of each drilled hole is a conductor pad formed

WO 03/019999

PCT/US02/26370

7

on the top surface of layer 112. Thus pad 136 is formed on the layer 112 at the hole 116A, and pads 138 are formed on the layer 112 in registration with the holes 116B. Pad 144 is formed on the layer 110 in registration with hole 140.

5 Each pad is connected to a plated through hole going to various layers within the PWB. At the various PWB layers are the DC/signal lines 146, DC powerplanes (i.e. a layer of copper or other conductor to which a voltage is applied), RF groundplanes 120, 122, and RF transmission lines

10 124. Pads 138 are connected to ground planes 122, 120 by plated through holes 148. Pad 136 is connected to the RF transmission line 124 by plated through hole 150. The DC signal pad 144 is connected to DC conductor trace 146 by plated through hole 152.

15 The package 50 can be mounted onto the PWB 100 using a variety of techniques, including adhesive film 160 as shown in FIGS. 4-5, mechanical clamps and threaded fasteners. The film 160 has a plurality of clearance holes 162 formed therein to receive therethrough the pins 60, 72, 76

20 when the package 50 is assembled to the PWB 100.

FIG. 5 is similar to FIG. 4, but illustrates the package 50 in an inserted, fully assembled state relative to the PWB 100. The tips of the pins 60, 72, 76 are brought into contact with the ends of the fuzz button interconnects 130, 132, 142, making electrical contact therewith. The package 50 is secured to the PWB 100 by the

25 adhesive film 160, which is preferably a double-sided adhesive layer structure.

The stripline conductor trace 124 on the top surface of layer 114 is not in contact with the RF ground plated through holes 148 on pads 138, but is routed between them as shown in FIG. 6. Here the RF conductor pad 136

30

WO 03/019999

PCT/US02/26370

8

contacting the RF center conductor plated through hole 150 is routed between the ground pads 138 and plated through holes 148.

5 The interconnect technique involves inserting the pins from the RF/DC module into the pre-drilled holes of the PWB containing the fuzz button interconnects. The pins compress the fuzz button contact against the conductor pad within the PWB and completing the connection to the various RF and DC/signal layers as shown in FIG. 5.

10 This new interconnect approach with this RF module hybrid package eliminates the need for coaxial connector and coaxial cables for the RF interconnection interfacing the PWB. Another advantage is that the mounting and attachment of the RF and DC/Signal interconnect uses the same assembly process so that all the interconnects can be
15 attached simultaneously.

Fuzz button interconnects offer a simple, cheap, and test friendly connection method. They are smaller and lighter than commercial coaxial connectors, and also allow
20 the RF module hybrid package also known as MIC (Microwave Integrated Circuit) package to be field removable and replaceable.

An exemplary use is to carry RF signals between MIC modules directly attached to a RF PWB, providing advantages
25 including low loss, minimal space, low cost, single mode transmission, and vertical transition. Applications can include vertical interconnects between stacked and removable RF assemblies, which can be found in receiver/exciters, communication subsystems, and other microwave circuits. Such circuits can be found in radar systems,
30 satellites, microwave automobile electronics, missiles

WO 03/019999

PCT/US02/26370

9

systems, and other applications where size is important (e.g. cellular phones).

5 It is understood that the above-described embodiments are merely illustrative of the possible specific embodiments which may represent principles of the present invention. Other arrangements may readily be devised in accordance with these principles by those skilled in the art without departing from the scope and spirit of the invention.

WO 03/019999

PCT/US02/26370

10

CLAIMSWhat is claimed is:

1. An RF electrical assembly, comprising:
an RF package (50) comprising:

an external housing (52) including a wall structure (54) having an interconnect opening (54A) formed therein;

an electrically conductive feed-through pin structure mounted in the interconnect opening, the pin structure including an elongated electrically conductive center pin (72) supported on a dielectric spacer element (74) in the interconnect opening, the center pin having an interior end disposed within the housing for connection to RF circuitry, and a distal end for interconnection with an interconnection structure external to the RF package;

a plurality of electrically conductive shield pins (76) connected to the wall structure and extending outwardly from the housing and disposed to surround an external portion of the center pin to form a coaxial shield structure; and

a multi-layer printed wiring board (PWB) (100) electrically connected to the RF package through said pin and coaxial shield structure, the PWB including:

a center pin hole (116A) formed through a first surface to a first predetermined depth;

a plurality of shield pin holes (116B) formed through said first surface to a second predetermined depth;

WO 03/019999

PCT/US02/26370

11

30 a center pin compressible wire interconnect structure (130) disposed in said center pin hole to make electrical contact with a distal tip of the center pin when the package is assembled to the PWB;

35 a plurality of shield pin compressible wire bundle interconnect structures (132) disposed in said shield pin holes to make electrical contact with respective distal tips of the shield pins when the package is assembled to the PWB.

2. An assembly according to Claim 1, wherein the compressible wire bundles (130, 132) are fabricated of densely packed thin gold plated wire.

3. An assembly according to Claim 1 or Claim 2, wherein the first predetermined distance is equal to the second predetermined distance.

4. An assembly according to any preceding claim, wherein the package further includes at least one DC signal pin (60) extending through the wall structure and having an interior end for connection to a DC circuit within the housing and an exterior end extending away from the wall structure for connection to a DC interconnect structure on the PWB.

5. An assembly according to Claim 4, wherein the DC interconnect structure includes a DC pin hole (140) formed through the first surface of the PWB to a third predetermined depth of said PWB, and a DC pin hole compressible wire bundle interconnect structure (142) disposed in said

WO 03/019999

PCT/US02/26370

12

pin hole to make electrical contact with the distal tip of the DC pin when the package is assembled to the PWB.

6. An assembly according to any preceding claim, wherein the PWB includes an RF stripline transmission line defined by first and second ground plane conductive layers (120, 122) sandwiching a stripline conductor (124) and
5 intervening dielectric layers (112, 114), and wherein said center pin compressible wire interconnect structure is in contact with a conductive pad or trace (136) in turn electrically connected to said stripline conductor, and
10 said shield pin compressible wire bundle interconnect structures are each in contact with a conductive pad or trace (138) in turn electrically connected to each of said first and second ground plane structures.

7. An assembly according to any preceding claim, further including an attachment structure (90) for securing the RF package to the PWB when the package is assembled to the PWB.

8. An assembly according to Claim 7, wherein the attachment structure includes an adhesive layer.

9. An assembly according to any preceding claim, wherein the housing is a metal housing.

10. An assembly according to any preceding claim, wherein the RF package includes a plurality of said RF interconnects, and the PWB includes for each RF interconnect a corresponding center hole pin, plurality of shield
5 pins holes, center pin compressible wire interconnect

WO 03/019999

PCT/US02/26370

13

structure, and shield pin compressible wire bundle interconnect structure, and circuitry connecting the compressible conductor interconnect structures to appropriate levels of the PWB for grounding and RF signal conduction.

WO 03/019999

1/4

PCT/US02/26370




Fig. 1C




Fig. 1B




Fig. 1A

WO 03/019999

2/4

PCT/US02/26370





Fig. 3



WO 03/019999

3/4

PCT/US02/26370




Fig. 4

WO 03/019999

4/4

PCT/US02/26370




Fig. 5




Fig. 6

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 02/26370

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H05K1/18 H05K3/32 H01L23/66

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H05K H01L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

PAJ, EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6 196 876 B1 (PAAGMAN) 6 March 2001 (2001-03-06) abstract; figures	1,6
A	US 4 816 791 A (CARNAHAN ET AL.) 28 March 1989 (1989-03-28) abstract; figure 2	1,6
A	EP 0 390 600 A (SONY CORP) 3 October 1990 (1990-10-03) abstract; figures	1,6,9,10
A	US 4 736 266 A (TANIBE) 5 April 1988 (1988-04-05) claims; figures	1,6,9,10



Further documents are listed in the continuation of box C.



Parent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

5 November 2002

Date of mailing of the international search report

12/11/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5018 Patentlaan 2
NL - 2260 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl
Fax (+31-70) 340-3016

Authorized officer

Mes, L

INTERNATIONAL SEARCH REPORT

International Application No.
PCT/US 02/26370

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6 031 188 A (PLUYMERS ET AL.) 29 February 2000 (2000-02-29) claims; figure 4	1,10
A	PATENT ABSTRACTS OF JAPAN vol. 015, no. 288 (E-1092), 22 July 1991 (1991-07-22) & JP 03 101197 A (MITSUBISHI ELECTRIC CORP), 25 April 1991 (1991-04-25) abstract	1,9
A	PATENT ABSTRACTS OF JAPAN vol. 016, no. 300 (E-1227), 2 July 1992 (1992-07-02) & JP 04 081112 A (NEC CORP); 13 March 1992 (1992-03-13) abstract	1
A	PATENT ABSTRACTS OF JAPAN vol. 009, no. 131 (E-319), 6 June 1985 (1985-06-06) & JP 60 016701 A (NEC CORP), 28 January 1985 (1985-01-28) abstract	1
A	US 4 988 306 A (HOPFER, III ET AL.) 29 January 1991 (1991-01-29) abstract; figures	1

INTERNATIONAL SEARCH REPORT

 International Application No
 PCT/US 02/26370

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 6196876	B1	06-03-2001	EP 0692841 A1 17-01-1996
			CN 1152972 A ,B 25-06-1997
			DE 69413679 D1 05-11-1998
			DE 69413679 T2 29-04-1999
			WO 9602958 A1 01-02-1996
			JP 10506223 T 16-06-1998
			TW 379870 Y 11-01-2000
			US 5961349 A 05-10-1999
US 4816791	A	28-03-1989	DE 3853135 D1 30-03-1995
			DE 3853135 T2 26-10-1995
			EP 0318311 A2 31-05-1989
EP 0390600	A	03-10-1990	JP 2260701 A 23-10-1990
			JP 2260499 A 23-10-1990
			DE 69010726 D1 25-08-1994
			DE 69010726 T2 12-01-1995
			EP 0390600 A2 03-10-1990
			US 5036301 A 30-07-1991
US 4736266	A	05-04-1988	JP 1761341 C 20-05-1993
			JP 4047998 B 05-08-1992
			JP 60250699 A 11-12-1985
			DE 3577968 D1 28-06-1990
			EP 0162474 A2 27-11-1985
			KR 8905141 B1 11-12-1989
US 6031188	A	29-02-2000	NONE
JP 03101197	A	25-04-1991	NONE
JP 04081112	A	13-03-1992	NONE
JP 60016701	A	28-01-1985	NONE
US 4988306	A	29-01-1991	CA 1313545 A1 09-02-1993
			CA 1314313 A1 09-03-1993
			DE 69032615 D1 08-10-1998
			DE 69032615 T2 15-04-1999
			DE 69034002 D1 10-10-2002
			EP 0429582 A1 05-06-1991
			EP 0838978 A2 29-04-1998
			ES 2120410 T3 01-11-1998
			JP 3506094 T 26-12-1991
			JP 3070762 B2 31-07-2000
			WO 9014750 A1 29-11-1990
			US 5597313 A 28-01-1997
			US 5013249 A 07-05-1991
			US 6062870 A 16-05-2000

Form PCT/ISA/210 (patent family annex) (July 1992)